

run_sjsdm_tuning_tier_round.R

September 10, 2026

Contents

run_sjsdm_tuning_tier_round 1

Index 3

run_sjsdm_tuning_tier_round
Run One sjSDM Tier Tuning Round

Description

Runs one explicit tier survivor or final artifact target without a nested callr boundary.

Usage

```
run_sjsdm_tuning_tier_round(  
  tuning_strategy = NULL,  
  tier_target_name = NULL,  
  fresh_round = FALSE,  
  final_round = FALSE,  
  run_pipeline_function = run_pipeline,  
  vec_allowed_profile_roles = base::c("main", "smoke"),  
  vec_allowed_profile_statuses = "active",  
  unit_store_suffixes = NULL  
)
```

Arguments

tuning_strategy, tier_target_name
Strategy and optional staged tier target.

fresh_round, final_round
First- and final-round flags.

run_pipeline_function
Injectable pipeline runner.

vec_allowed_profile_roles, vec_allowed_profile_statuses
Allowed profile metadata forwarded to the runner.

unit_store_suffixes
Optional successful spatial-unit suffixes included in tier aggregation.

2

run_sjsdm_tuning_tier_round

Value

Invisible 'NULL'.

Index

run_sjsdm_tuning_tier_round, [1](#)