

# select\_sjsdm\_regularization.R

September 10, 2026

## Contents

|                                       |          |
|---------------------------------------|----------|
| select_sjsdm_regularization . . . . . | 1        |
| <b>Index</b>                          | <b>3</b> |

---

|                                    |
|------------------------------------|
| select_sjsdm_regularization        |
| <i>Select sjSDM Regularization</i> |

---

## Description

Selects one regularization candidate from repeat-level tuning summaries.

## Usage

```
select_sjsdm_regularization(  
  data_tuning_summary = NULL,  
  selection_metric = "negative_log_likelihood_per_response"  
)
```

## Arguments

|                     |                                                                                                                                     |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| data_tuning_summary | Repeat-by-candidate table returned by [summarise_sjsdm_tuning_candidates()].                                                        |
| selection_metric    | Metric minimized during selection. Defaults to normalized held-out negative log likelihood, "negative_log_likelihood_per_response". |

## Details

A candidate is eligible only when every represented repeat is complete. The selection metric is averaged equally across repeats. Lower values are preferred, and exact ties are resolved by lexical candidate identifier.

## Value

One-row tibble containing the selected candidate parameters, criterion name and value, repeat count, deterministic candidate rank, and regularization source.

**Examples**

```
## Not run:  
select_sjsdm_regularization(data_tuning_summary = data_summary)  
  
## End(Not run)
```

# Index

`select_sjsdm_regularization`, [1](#)