

# validate\_config\_profile\_selection.R

July 27, 2026

## Contents

|                                             |          |
|---------------------------------------------|----------|
| validate_config_profile_selection . . . . . | 1        |
| <b>Index</b>                                | <b>2</b> |

---

|                                                            |
|------------------------------------------------------------|
| validate_config_profile_selection                          |
| <i>Validate the Active Configuration Profile Selection</i> |

---

## Description

Checks that the active profile is explicitly authorized for a runner.

## Usage

```
validate_config_profile_selection(  
  vec_allowed_roles = base::c("main", "smoke"),  
  vec_allowed_statuses = "active",  
  file = here::here("config.yml")  
)
```

## Arguments

|                      |                                                                                                                                          |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| vec_allowed_roles    | Non-empty character vector of profile roles authorized by the caller. Production runners should retain the default 'c("main", "smoke")'. |
| vec_allowed_statuses | Non-empty character vector of profile statuses authorized by the caller. Production runners should retain the default '"active"'.        |
| file                 | Path to the generated YAML configuration file.                                                                                           |

## Details

Base and archived profiles are never executable. Main and smoke profiles must also declare 'selectable: true'. Dedicated reference or one-time runners may explicitly authorize their role and status.

**Value**

The validated ‘\_profile’ metadata, invisibly.

# Index

`validate_config_profile_selection`, [1](#)