

# resolve\_trait\_taxon\_ids.R

August 13, 2026

## Contents

|                                   |          |
|-----------------------------------|----------|
| resolve_trait_taxon_ids . . . . . | 1        |
| <b>Index</b>                      | <b>3</b> |

---

resolve\_trait\_taxon\_ids

*Resolve Trait Taxon IDs to Taxon Names*

---

## Description

Replaces numeric ‘taxon\_id’ values in a cleaned trait data frame with the corresponding ‘taxon\_name’ from the ‘Taxa’ table in the VegVault SQLite database. Rows with unresolved IDs receive ‘NA’ for ‘taxon\_name’ (standard left-join behaviour).

## Usage

```
resolve_trait_taxon_ids(  
  data_trait_records,  
  path_vegvault = here::here("Data/Input/VegVault.sqlite")  
)
```

## Arguments

`data_trait_records` A data frame with at least the column ‘taxon\_id’ (integer or numeric), typically the output of `[filter_complete_trait_records()]`.

`path_vegvault` A single character string giving the path to the VegVault SQLite database (default: `here::here("Data/Input/VegVault.sqlite")`).

## Details

Opens a fresh database connection, loads the ‘Taxa’ table, filters it to only the IDs present in ‘data\_trait\_records’, performs a left join, and closes the connection via ‘on.exit()’.

## Value

A tibble with ‘taxon\_name’, all source identifiers, and the trait fields. The original ‘taxon\_id’ is retained for auditability.

**See Also**

[[filter\\_complete\\_trait\\_records\(\)](#)], [[load\\_continental\\_trait\\_records\\_from\\_vegvault\(\)](#)]

# Index

`resolve_trait_taxon_ids`, [1](#)