

get_taxa_classification.R

April 27, 2026

Contents

get_taxa_classification	1
Index	3

get_taxa_classification	<i>Get Taxa Classification</i>
-------------------------	--------------------------------

Description

Retrieves taxonomic classification for a vector of taxa using the taxospace package. Filters results to include only plant taxa. Results are cached on disk so that repeated calls for the same taxa avoid redundant HTTP requests.

Usage

```
get_taxa_classification(  
  data = NULL,  
  cache_dir = here::here("Data/Temp/taxospace")  
)
```

Arguments

data	A character vector of taxon names to classify.
cache_dir	Character scalar. Path to the directory where per-taxon classification results are cached as ‘.qs’ files (using the qs2 package). The directory is created automatically if it does not exist. The default is ‘here::here("Data/Temp/taxospace”)’.

Details

Uses ‘taxospace::get_classification()’ to retrieve classification. Flags and filters for plant taxa (kingdom Plantae). Before calling the taxospace service, checks for a cached ‘.qs’ file in ‘cache_dir’. A successful result is saved to cache; the empty dummy tibble returned on failure is never cached.

Value

A data frame with columns ‘sel_name’, ‘name’, ‘rank’, and ‘id’. Returns an empty tibble with those columns when no plant taxa are found or the taxospace service returns no classification.

See Also

[taxospace::get_classification()], [qs2::qs_read()], [qs2::qs_save()]

Index

`get_taxa_classification`, [1](#)