

compute_cross_validation_grid_calibration_from_resolution

August 31, 2026

Contents

compute_cross_validation_grid_calibration_from_resolution	1
Index	3

compute_cross_validation_grid_calibration_from_resolution
<i>Calibrate Cross-Validation Grid From Fold Resolution</i>

Description

Runs spatial-grid calibration only when the resolved cross-validation strategy uses spatially stratified grouped folds.

Usage

```
compute_cross_validation_grid_calibration_from_resolution(  
  data_locations = NULL,  
  data_fold_resolution = NULL,  
  candidate_grid_cell_sizes_km = NULL,  
  n_repeats = 1L,  
  occupancy_criterion = "median",  
  target_locations_per_cell = NULL,  
  lower_quantile_probability = 0.25,  
  max_fold_location_difference = 1L,  
  max_fold_sample_difference = Inf,  
  seed = 900723L  
)
```

Arguments

`data_locations` Location table returned by [build_cross_validation_location_table()].

`data_fold_resolution` One-row table returned by [resolve_cross_validation_fold_count()].

`candidate_grid_cell_sizes_km` Numeric vector of candidate grid-cell widths in kilometres.

`n_repeats` Positive integer number of deterministic assignment repeats.
`occupancy_criterion, target_locations_per_cell`
`lower_quantile_probability, max_fold_location_difference, max_fold_sample_difference, seed`
 Arguments passed to `[compute_cross_validation_grid_calibration()]`.

Value

Grid-calibration tibble. Leave-one-location-out and no-holdout strategies return a zero-row tibble with the stable calibration schema.

Examples

```
data_locations <-
  tibble::tibble(
    location_id = base::letters[1:6],
    coord_x_km = base::seq_len(6L),
    coord_y_km = base::seq_len(6L),
    n_samples = base::rep(1L, 6L),
    row_indices = base::as.list(base::seq_len(6L))
  )
data_resolution <-
  resolve_cross_validation_fold_count(6L, 5L)
compute_cross_validation_grid_calibration_from_resolution(
  data_locations = data_locations,
  data_fold_resolution = data_resolution,
  candidate_grid_cell_sizes_km = c(1, 10)
)
```

Index

`compute_cross_validation_grid_calibration_from_resolution,`
[1](#)