

# load\_project\_functions.R

August 31, 2026

## Contents

|                                  |   |
|----------------------------------|---|
| load_project_functions . . . . . | 1 |
|----------------------------------|---|

|              |          |
|--------------|----------|
| <b>Index</b> | <b>3</b> |
|--------------|----------|

---

|                        |                               |
|------------------------|-------------------------------|
| load_project_functions |                               |
|                        | <i>Load Project Functions</i> |

---

## Description

Validates and deterministically loads the active project function tree.

## Usage

```
load_project_functions(  
  path_function_root,  
  environment_target,  
  vec_excluded_directory_names = base::character()  
)
```

## Arguments

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| path_function_root           | A single existing directory containing project function files.             |
| environment_target           | The environment into which validated functions are loaded.                 |
| vec_excluded_directory_names | Character vector of exact directory names to exclude with all descendants. |

## Details

Validation occurs before any function is loaded. Each active file must contain exactly one top-level function declaration and no other top-level expressions. Function names must match file basenames; a single leading dot is allowed for an internal function. Duplicate symbols and case-insensitive duplicate basenames are rejected.

**Value**

A data frame describing the validated functions in source order.

**Examples**

```
## Not run:  
load_project_functions(  
  path_function_root = here::here("R/Functions"),  
  environment_target = base::globalenv()  
)  
  
## End(Not run)
```

# Index

`load_project_functions`, [1](#)