

# resolve\_cross\_validation\_fold\_count.R

August 31, 2026

## Contents

|                                               |          |
|-----------------------------------------------|----------|
| resolve_cross_validation_fold_count . . . . . | 1        |
| <b>Index</b>                                  | <b>3</b> |

---

|                                            |
|--------------------------------------------|
| resolve_cross_validation_fold_count        |
| <i>Resolve Cross-Validation Fold Count</i> |

---

## Description

Resolves the smallest viable location-level fold count from a default toward leave-one-location-out while preserving a minimum training-location count.

## Usage

```
resolve_cross_validation_fold_count(  
  n_locations = NULL,  
  min_train_locations = NULL,  
  default_folds = 5L  
)
```

## Arguments

|                     |                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------|
| n_locations         | Single positive integer. Number of unique sampling locations available.                                          |
| min_train_locations | Single positive integer. Minimum number of locations required in every training partition and in the full model. |
| default_folds       | Single integer greater than one. Preferred grouped fold count. Defaults to '5L'.                                 |

## Details

Balanced grouped folds are assessed using the largest possible test fold, 'ceiling(n\_locations / effective\_folds)'. If the preferred fold count would remove too many locations, fold count increases until every training partition is viable. A fold count equal to 'n\_locations' is classified as leave-one-location-out. A full-model-viable ID with no viable holdout is classified for tier-pooled regularization. Other sample, response, and MEM checks belong to the separate CV feasibility assessment.

**Value**

One-row tibble with 'n\_locations', 'default\_folds', 'effective\_folds', 'min\_train\_locations', 'min\_training\_locations\_act', 'cv\_strategy', and 'cv\_feasibility\_status'. 'effective\_folds' is 'NA' when location-level holdout is infeasible.

**Examples**

```
resolve_cross_validation_fold_count(  
  n_locations = 7L,  
  min_train_locations = 5L  
)
```

# Index

`resolve_cross_validation_fold_count, 1`