

run_decomposition_upstream_refresh.R

August 31, 2026

Contents

run_decomposition_upstream_refresh	1
Index	2

run_decomposition_upstream_refresh
<i>Refresh CZ Decomposition Upstream Targets</i>

Description

Refreshes or validates the CZ paleo resolution-test target store.

Usage

```
run_decomposition_upstream_refresh(  
  refresh_upstream = TRUE,  
  store_path = here::here("Data/targets/cz_paleo/pipeline_paleo_resolution_test"),  
  pipeline_script = "R/Pipelines/pipeline_paleo_resolution_test.R",  
  run_pipeline_fn = run_pipeline,  
  tar_meta_fn = targets::tar_meta,  
  verbose = TRUE  
)
```

Arguments

refresh_upstream	Logical. If 'TRUE', rebuilds the upstream targets before validation.
store_path	Targets store path to validate.
pipeline_script	Pipeline script used for the upstream refresh.
run_pipeline_fn	Pipeline runner. Defaults to 'run_pipeline()'.
tar_meta_fn	Metadata reader. Defaults to 'targets::tar_meta()'.
verbose	Logical. If 'TRUE', progress messages are printed.

2

run_decomposition_upstream_refresh

Value

One-row tibble with refresh metadata and validation status.

Index

run_decomposition_upstream_refresh, [1](#)