

run_sjsdm_selected_fold.R

August 31, 2026

Contents

run_sjsdm_selected_fold	1
Index	3

run_sjsdm_selected_fold	
	<i>Run One Selected sjSDM Fold</i>

Description

Prepares, fits, and predicts one live selected-candidate fold, then delegates all persisted row construction to [build_sjsdm_selected_fold_artifacts()].

Usage

```
run_sjsdm_selected_fold(  
  list_fold_context = NULL,  
  data_candidate = NULL,  
  data_sample_ids = NULL,  
  taxon_names = NULL,  
  regularization_source = NULL,  
  prepare_fold_function = NULL,  
  fit_function = NULL,  
  predict_function = NULL,  
  seed = 900723L  
)
```

Arguments

- list_fold_context
Fold context returned by [build_sjsdm_tuning_fold_context()].
- data_candidate One-row selected candidate table without provenance-only fields.
- data_sample_ids, taxon_names
Normalized sample metadata and full ordered response-taxon names.
- regularization_source
Source label for the selected regularization candidate.

prepare_fold_function, fit_function, predict_function

Injectable selected-fold lifecycle functions.

seed

Non-negative base integer used to derive the stable fold fit seed.

Value

Named list with one fold's prediction and diagnostic artifacts.

Index

run_sjsdm_selected_fold, 1