

# save\_missing\_taxa\_template.R

August 31, 2026

## Contents

save\_missing\_taxa\_template . . . . . 1

**Index** 3

---

save\_missing\_taxa\_template  
*Save the shared missing-taxa template*

---

## Description

Reads the existing missing-taxa template CSV (if present), removes any entries that are now present in ‘data\_classification\_table’ (i.e. have since been classified), appends any new unclassified taxa, deduplicates by ‘sel\_name’, and writes the result back to disk. If the file does not yet exist it is created. Nothing is written when ‘data\_missing\_taxa’ is empty, the file already exists, and no stale entries need to be removed.

## Usage

```
save_missing_taxa_template(  
  data_missing_taxa,  
  file_missing_taxa_template = here::here("Data/Input/missing_taxa_template.csv"),  
  data_classification_table = NULL  
)
```

## Arguments

**data\_missing\_taxa**  
A tibble with columns ‘sel\_name’, ‘kingdom’, ‘phylum’, ‘class’, ‘order’, ‘family’, ‘genus’, and ‘species’ (all character). Rows represent taxa that could not be classified. Pass an empty tibble (zero rows) when there are no new missing taxa.

**file\_missing\_taxa\_template**  
A length-1 character string giving the path to the CSV file. Defaults to ‘here::here("Data/Input/missing\_taxa\_template.csv")’.

**data\_classification\_table**  
‘NULL’ (default) or a data frame with at least a ‘sel\_name’ column. When provided, any entry already present in the existing template whose ‘sel\_name’ also appears in this table is removed from the template before merging. This prevents stale entries from re-appearing after a taxon has been manually added to the auxiliary classification table.

**Details**

The file is only written when at least one of the following is true:

- ‘data\_missing\_taxa’ contains one or more rows.
- The file at ‘file\_missing\_taxa\_template’ does not yet exist.
- ‘data\_classification\_table’ is not ‘NULL’ and at least one existing template entry is now classified.

Deduplication keeps the first occurrence of each ‘sel\_name’.

**Value**

The ‘file\_missing\_taxa\_template’ string (invisibly), so it can be used as a ‘format = "file"’ target return value in a targets pipeline.

**See Also**

[load\_auxiliary\_classification\_table()], [select\_unclassified\_taxa()], [validate\_taxa\_classification\_coverage()]

# Index

save\_missing\_taxa\_template, [1](#)