

build_cross_validation_assignments_from_resolution.R

September 15, 2026

Contents

build_cross_validation_assignments_from_resolution	1
Index	3

build_cross_validation_assignments_from_resolution
<i>Make Cross-Validation Assignments From Fold Resolution</i>

Description

Dispatches a resolved cross-validation strategy to spatially stratified or leave-one-location-out assignment while preserving one assignment schema.

Usage

```
build_cross_validation_assignments_from_resolution(  
  data_locations = NULL,  
  data_fold_resolution = NULL,  
  data_grid_calibration = NULL,  
  n_repeats = 1L,  
  seed = 900723L,  
  assignment_source = "per_id"  
)
```

Arguments

data_locations	Location table returned by [build_cross_validation_location_table()].
data_fold_resolution	One-row table returned by [resolve_cross_validation_fold_count()].
data_grid_calibration	Table returned by [compute_cross_validation_grid_calibration_from_resolution()].
n_repeats	Positive integer number of deterministic spatial assignment repeats.
seed	Non-negative integer assignment seed.
assignment_source	Non-empty character scalar recording assignment provenance.

Value

Tibble with the shared assignment columns plus 'cv_strategy' and 'assignment_source'. A no-holdout resolution returns a zero-row tibble with the same schema.

Examples

```
data_locations <-  
  tibble::tibble(  
    location_id = base::letters[1:6],  
    coord_x_km = base::seq_len(6L),  
    coord_y_km = base::seq_len(6L),  
    n_samples = base::rep(1L, 6L),  
    row_indices = base::as.list(base::seq_len(6L))  
  )  
data_resolution <-  
  resolve_cross_validation_fold_count(6L, 5L)  
build_cross_validation_assignments_from_resolution(  
  data_locations = data_locations,  
  data_fold_resolution = data_resolution,  
  data_grid_calibration = tibble::tibble()  
)
```

Index

build_cross_validation_assignments_from_resolution,
1