

build_sjsdm_tuning_schedule.R

September 23, 2026

Contents

build_sjsdm_tuning_schedule 1

Index 3

build_sjsdm_tuning_schedule
Build an sjSDM Tuning Schedule

Description

Validates exhaustive or staged cross-validation tuning settings and builds the deterministic repeat-level candidate budget used by every model pipeline.

Usage

```
build_sjsdm_tuning_schedule(  
  tuning_strategy = NULL,  
  n_candidates = NULL,  
  repeat_ids = NULL,  
  survivor_counts = NULL,  
  cv_strategy = NULL  
)
```

Arguments

tuning_strategy	Character scalar. Either "exhaustive" or "staged".
n_candidates	Positive integer number of regularization candidates.
repeat_ids	Unique positive integer repeat identifiers in execution order.
survivor_counts	Integer counts retained after each non-final staged round. Ignored for exhaustive tuning.
cv_strategy	Optional resolved CV strategy. Leave-one-location-out has only one unique assignment repeat, so it uses one exhaustive round even when staged tuning is configured for grouped CV.

Value

Tibble with one row per tuning round and columns 'tuning_strategy', 'strategy_version', 'round_id', 'repeat_id', 'n_candidates_entering', and 'n_candidates_surviving'.

Examples

```
build_sjsdm_tuning_schedule(  
  tuning_strategy = "staged",  
  n_candidates = 8L,  
  repeat_ids = 1:3,  
  survivor_counts = c(4L, 2L)  
)
```

Index

`build_sjsdm_tuning_schedule`, [1](#)