

diagnose_sjsdm_cv_preparation_endpoints.R

September 15, 2026

Contents

diagnose_sjsdm_cv_preparation_endpoints	1
Index	3

diagnose_sjsdm_cv_preparation_endpoints
<i>Diagnose sjSDM CV Preparation Endpoints</i>

Description

Diagnoses whether requested prepared-fold targets exist, have successful metadata and content hashes, and can be read from a targets store.

Usage

```
diagnose_sjsdm_cv_preparation_endpoints(  
  store_path = NULL,  
  target_names = NULL,  
  load_metadata_function = load_targets_store_metadata,  
  read_target_function = targets::tar_read_raw  
)
```

Arguments

store_path	Character scalar identifying the targets store.
target_names	Unique non-empty character vector of prepared-fold target names.
load_metadata_function	Injectable target-metadata loader.
read_target_function	Injectable raw target reader.

Details

Endpoint statuses are ‘prepared’, ‘missing’, ‘errored’, ‘unreadable’, or ‘cache_format_incompatible’. The last status is reserved for legacy ‘qs’ objects that current ‘qs2’-based targets installations cannot read.

Value

A tibble with one row per requested target and its endpoint status, data hash, and diagnostic message.

Index

diagnose_sjsdm_cv_preparation_endpoints,
[1](#)