

evaluate_sjsdm_cross_validated_predictions.R

September 15, 2026

Contents

evaluate_sjsdm_cross_validated_predictions	1
Index	3

evaluate_sjsdm_cross_validated_predictions
<i>Evaluate sjSDM Cross-Validated Predictions</i>

Description

Pools selected-candidate out-of-fold predictions within each repeat and taxon, then calculates taxon and community predictive metrics.

Usage

```
evaluate_sjsdm_cross_validated_predictions(  
  data_predictions = NULL,  
  epsilon = 1e-06  
)
```

Arguments

data_predictions	Long selected-candidate prediction table returned in the data-prediction element of [run_sjsdm_selected_candidate_folds()].
epsilon	Probability clipping tolerance passed to [evaluate_binary_log_loss()]. Defaults to 1e-6.

Details

Folds are pooled before metrics are calculated. Any non-ok prediction row makes all metrics for that repeat and taxon incomplete. One-class pooled responses retain the metric-specific undefined statuses from the binary evaluators, while binary log loss remains evaluable.

Value

Named list containing `data_taxon_metrics` and `data_community_summary`. Taxon metrics have one row per repeat, taxon, and metric. Community summaries contain the mean finite estimate across evaluable taxa for each repeat and metric.

Examples

```
## Not run:  
evaluate_sjsdm_cross_validated_predictions(  
  data_predictions = data_predictions  
)  
  
## End(Not run)
```

Index

`evaluate_sjsdm_cross_validated_predictions,`
[1](#)