

load_model_tuning_parameters.R

September 15, 2026

Contents

load_model_tuning_parameters	1
Index	3

load_model_tuning_parameters
<i>Get Model Tuning Parameters</i>

Description

Reads model-fitting parameters for one analysis, spatial unit, and resolution from the model tuning CSV catalogue.

Usage

```
load_model_tuning_parameters(  
  analysis_id,  
  scale_id,  
  resolution_id,  
  dir = here::here("Data/Input/Model_tuning"),  
  fit_stage = c("final", "cross_validation")  
)
```

Arguments

analysis_id	A single non-empty character string identifying the analysis family, such as "paleo_spatial" or "modern_spatial".
scale_id	A single non-empty character string identifying the spatial unit. Must match exactly one row in the selected tuning file.
resolution_id	A single character string identifying the model resolution. "genus" reads the *_genus.csv file, "family" reads the *_family.csv file, and "functional_type", "ft_paleo", and "ft_modern" read the *_ft.csv file.
dir	Directory containing model tuning CSV files. Default: here::here("Data/Input/Model_tuning").
fit_stage	Fitting stage to load. "final" returns the historical full-data model budget. "cross_validation" returns the independent CV fit budget.

Value

A named stage-specific fitting list. Missing step-size and early-stopping values are returned as 'NULL'.

Index

`load_model_tuning_parameters`, [1](#)