

load_sjsdm_available_tier_decisions.R

September 15, 2026

Contents

load_sjsdm_available_tier_decisions 1

Index 2

load_sjsdm_available_tier_decisions
Collect Available sjSDM Tier Decisions

Description

Discovers consecutive completed staged-round decisions in the isolated tier store. A missing next round is a normal orchestration boundary; errored targets, decision gaps, and malformed existing artifacts abort.

Usage

```
load_sjsdm_available_tier_decisions(  
  store_path = NULL,  
  data_model_context = NULL,  
  n_non_final_rounds = NULL,  
  read_meta_function = load_targets_store_metadata,  
  read_decision_function = load_sjsdm_tier_survivor_decisions  
)
```

Arguments

`store_path` Character scalar path to the dedicated tier-tuning targets store.

`data_model_context` One-row model-context table used to select decision rows.

`n_non_final_rounds` Non-negative integer count of rounds that publish survivor decisions.

`read_meta_function` Injectable metadata reader compatible with [load_targets_store_metadata()].

`read_decision_function` Injectable decision reader compatible with [load_sjsdm_tier_survivor_decisions()].

Value

Ordered list of consecutive decision tibbles beginning with round one.

Index

`load_sjsdm_available_tier_decisions`, [1](#)