

run_pipeline_progress_monitor.R

September 15, 2026

Contents

run_pipeline_progress_monitor 1

Index 3

run_pipeline_progress_monitor
Monitor Pipeline Progress

Description

Opens the official ‘targets’ dashboard for a pipeline target store.

Usage

```
run_pipeline_progress_monitor(  
  sel_script,  
  sel_config,  
  store_suffix = NULL,  
  seconds_refresh = 10,  
  sel_initial_display = "branches",  
  flag_refresh_automatically = FALSE,  
  verbose = TRUE  
)
```

Arguments

sel_script	Path to the pipeline script, relative to the project root or absolute.
sel_config	Configuration key in ‘config.yml’ whose ‘target_store’ contains the selected pipeline output.
store_suffix	Optional nested target store identifier inserted between ‘target_store’ and the pipeline script name, such as “europe” or “eu_r005_l014”.
seconds_refresh	Positive finite refresh interval in seconds. Used only when automatic refresh is enabled in the dashboard. Default is ‘10’.

<code>sel_initial_display</code>	Initial official ‘targets’ dashboard tab. One of “summary”, “branches”, “progress”, “graph”, or “about”.
<code>flag_refresh_automatically</code>	Logical indicating whether dashboard periodic refresh starts enabled. Default is ‘FALSE’.
<code>verbose</code>	Logical indicating whether to display launch information. Default is ‘TRUE’.

Details

The target store is resolved using the same layout as `[run_pipeline()]`: ‘target_store/pipeline_name/’ when ‘store_suffix’ is ‘NULL’, and ‘target_store/store_suffix/pipeline_name/’ otherwise. The app always uses ‘targets_only = TRUE’ and ‘outdated = FALSE’ to keep monitoring fast. Stop a running monitor with ‘Ctrl+C’.

Value

No return value. The dashboard runs in the foreground until stopped.

See Also

`[run_pipeline()]`, `[targets::tar_watch_ui()]`, `[targets::tar_watch_server()]`

Examples

```
## Not run:
run_pipeline_progress_monitor(
  sel_script = "R/Pipelines/pipeline_paleo_spatial_resolution.R",
  sel_config = "project_paleo_spatial_continental",
  store_suffix = "europe"
)

run_pipeline_progress_monitor(
  sel_script = "R/Pipelines/pipeline_paleo_core.R",
  sel_config = "project_cz_paleo"
)

## End(Not run)
```

Index

`run_pipeline_progress_monitor`, [1](#)