

run_sjsdm_cv_calibration_rung.R

September 23, 2026

Contents

run_sjsdm_cv_calibration_rung	1
---	---

Index	3
--------------	----------

run_sjsdm_cv_calibration_rung
<i>Run One sjSDM CV Calibration Budget Rung</i>

Description

Fits and scores every regularization candidate over cached prepared folds for one or more repeats at one fixed iteration and sampling budget.

Usage

```
run_sjsdm_cv_calibration_rung(  
  data_candidates = NULL,  
  list_prepared_folds = NULL,  
  data_budget = NULL,  
  sel_abiotic_formula = NULL,  
  config_sjsdm_cv_fitting = NULL,  
  repeat_ids = 1L,  
  fold_ids = NULL,  
  work_checkpoint_file = NULL,  
  calibration_stage = "calibration",  
  seed = 900723L,  
  device = "gpu",  
  candidate_fit_function = fit_sjsdm_cross_validation_candidate,  
  predict_function = predict_sjsdm_probability_matrix,  
  score_function = score_sjsdm_joint_tuning_predictions,  
  verbose = TRUE  
)
```

Arguments

<code>data_candidates</code>	Complete regularization candidate table.
<code>list_prepared_folds</code>	Cached fold records from <code>[prepare_sjsdm_tuning_folds()]</code> .
<code>data_budget</code>	One-row calibration ladder entry.
<code>sel_abiotic_formula, config_sjsdm_cv_fitting</code>	Model formula and validated structural CV fitting configuration.
<code>repeat_ids</code>	Integer repeats to execute.
<code>fold_ids</code>	Optional positive integer fold IDs to retain. 'NULL' keeps all folds.
<code>work_checkpoint_file</code>	Optional '.qs' file that persists each completed candidate-fold result.
<code>calibration_stage</code>	Character label used in progress messages and checkpoint provenance.
<code>seed, device</code>	Deterministic seed and fitting device.
<code>candidate_fit_function, predict_function, score_function</code>	Injectable fitting, prediction, and scoring backends.
<code>verbose</code>	Logical. If 'TRUE', progress is printed to the console.

Value

List containing fold-level benchmark evidence and attempt-level provenance.

Index

run_sjsdm_cv_calibration_rung, [1](#)