

# join\_sample\_ages.R

July 29, 2026

## Contents

|                            |          |
|----------------------------|----------|
| join_sample_ages . . . . . | 1        |
| <b>Index</b>               | <b>3</b> |

---

|                  |                         |
|------------------|-------------------------|
| join_sample_ages | <i>Join Sample Ages</i> |
|------------------|-------------------------|

---

## Description

Joins sample ages to records using dataset and sample identifiers.

## Usage

```
join_sample_ages(data_records = NULL, data_sample_ages = NULL)
```

## Arguments

- data\_records     A data frame containing ‘dataset\_name’ and ‘sample\_name’.
- data\_sample\_ages     A data frame containing ‘dataset\_name’, ‘sample\_name’, and ‘age’.

## Details

The age table must have at most one row per dataset-sample key. Unmatched records are retained with a missing age.

## Value

‘data\_records’ with the matching ‘age’ column joined.

**Examples**

```
data_records <-  
  tibble::tibble(  
    dataset_name = "example",  
    sample_name = "sample_1",  
    value = 10  
  )  
data_sample_ages <-  
  tibble::tibble(  
    dataset_name = "example",  
    sample_name = "sample_1",  
    age = 100  
  )  
  
join_sample_ages(  
  data_records = data_records,  
  data_sample_ages = data_sample_ages  
)
```

# Index

`join_sample_ages`, [1](#)