

render_trait_qc_pdf.R

July 30, 2026

Contents

render_trait_qc_pdf	1
Index	3

render_trait_qc_pdf	<i>Render Trait QC Report to a Compressed PDF</i>
---------------------	---

Description

Renders 'Trait_qc_report.qmd' to a dated PDF for a single trait domain (or for all domains when 'sel_domain_filter' is 'NULL'), moves the rendered file from the Quarto docs output directory to 'path_output_dir', and compresses it in-place with 'qpdf::pdf_compress()'.

The output filename follows one of two patterns depending on 'sel_domain_filter': - 'NULL': 'trait_qc_report_Sys.Date().pdf' - character: 'trait_qc_<slug>_Sys.Date().pdf' where '<slug>' is 'sel_domain_filter' with all non-alphanumeric characters replaced by underscores.

Usage

```
render_trait_qc_pdf(  
  sel_domain_filter = NULL,  
  path_output_dir = here::here("Outputs/Reports"),  
  path_qmd = here::here("R/03_Supplementary_analyses/_Trait_qc/Trait_qc_report.qmd"),  
  path_docs_dir = here::here("docs/R/03_Supplementary_analyses/_Trait_qc"),  
  sel_max_pages = NULL,  
  minimum_records_taxonomic = 5L,  
  verbose = TRUE  
)
```

Arguments

sel_domain_filter
Character scalar or 'NULL'. When 'NULL', all domains are rendered into a single PDF. When a character scalar, only taxa from that trait domain are included. Default: 'NULL'.

path_output_dir
Character scalar. Directory where the compressed PDF is saved. Default: 'here::here("Outputs/Reports")'.

<code>path_qmd</code>	Character scalar. Path to the Quarto source document. Default: <code>'here::here("R/03_Supplementary_analyses/_Trait_qc/Trait_qc_report.qmd")'</code> .
<code>path_docs_dir</code>	Character scalar. Directory that Quarto writes its output to before the file is moved. Default: <code>'here::here("docs/R/03_Supplementary_analyses/_Trait_qc")'</code> .
<code>sel_max_pages</code>	Positive integer scalar or <code>'NULL'</code> . Maximum number of pages to render. When <code>'NULL'</code> (default) there is no cap.
<code>minimum_records_taxonomic</code>	Positive integer scalar. Minimum records per taxon required for inclusion in the taxonomic comparison panel. Default: <code>'5L'</code> .
<code>verbose</code>	Logical. If <code>'TRUE'</code> (default), a progress message with the output path is printed to the console via <code>'cli::cli_inform()'</code> . A warning is emitted via <code>'cli::cli_warn()'</code> if the rendered file cannot be found.

Details

The function calls `'quarto::quarto_render()'` with `'execute_params'` set to `'sel_max_pages'`, `'minimum_records_taxonomic'`, and `'sel_domain_filter'`. The rendered file is expected at `'file.path(path_docs_dir, <output_filename>')'`. If found it is moved to `'path_output_dir'` and compressed; if not found a warning is emitted and nothing is moved.

Value

Invisible `'NULL'`. Called for its side effects: rendering and moving a PDF to `'path_output_dir'`.

See Also

`[generate_trait_qc_report()]`

Index

`render_trait_qc_pdf`, [1](#)