

extract_data_from_vegvault.R

April 21, 2026

Contents

extract_data_from_vegvault	1
Index	3

extract_data_from_vegvault
<i>Extract Data from VegVault</i>

Description

Extracts data from the VegVault SQLite database based on specified geographic, temporal, and dataset type constraints.

Usage

```
extract_data_from_vegvault(  
  path_to_vegvault = here::here("Data/Input/VegVault.sqlite"),  
  x_lim = NULL,  
  y_lim = NULL,  
  age_lim = NULL,  
  sel_dataset_type = NULL,  
  sel_abiotic_var_name = NULL  
)
```

Arguments

path_to_vegvault	A character string specifying the path to the VegVault SQLite database (default: "Data/Input/VegVault.sqlite").
x_lim	A numeric vector of length 2 specifying the longitude range.
y_lim	A numeric vector of length 2 specifying the latitude range.
age_lim	A numeric vector of length 2 specifying the age range.
sel_dataset_type	A character vector specifying the dataset types to select.
sel_abiotic_var_name	A character vector specifying the abiotic variable names to select.

Details

The function performs the following steps:

1. Validates input parameters.
2. Checks the presence of the VegVault SQLite database.
3. Builds the vaultkeepr query plan (lazy SQL). If vaultkeepr raises an error during plan assembly (e.g. insufficient data for the specified constraints), the error is caught and re-thrown via `'cli::cli_abort()'` with the original message preserved.
4. Retrieves abiotic data and taxa information.
5. Returns the extracted data as a data frame.

Value

A data frame containing the extracted data.

Index

`extract_data_from_vegvault`, [1](#)