Aggregate sjSDM Tuning by Tier

Description

Aggregates normalized candidate loss within source IDs and then across a compatible spatial tier using equal source-ID weighting.

Usage

```
aggregate_sjsdm_tuning_by_tier(
  data_tuning_summary = NULL,
  include_sample_weighted = TRUE
)
```

Arguments

`data_tuning_summary`	Repeat-level tuning summaries from [summarise_sjsdm_tuning_candidates()] with source and model-context columns.
`include_sample_weighted`	Logical scalar. When true, also reports a sensitivity selection weighted by the number of observed response values contributed by each source ID.

Details

Input rows must describe one tier, taxonomic resolution, response family, predictor structure, and candidate-table hash. Every source ID must provide the same candidate identifiers and parameter values. Candidates with an incomplete result for any source ID remain visible but are not selectable. Staged searches may contribute different repeat counts by candidate and source; each source-candidate loss averages all available repeat evidence. A source with no complete candidate is omitted from pooled selection, using the same eligibility rule as production tier-survivor selection.

Value

Named list with source_candidate_loss, candidate_aggregation, and selection_sensitivity tibbles. The primary selection always uses equal source-ID weighting.

Examples

```
## Not run:
aggregate_sjsdm_tuning_by_tier(
  data_tuning_summary = data_tuning_summary
```

```
)


## End(Not run)
```