Make Cross-Validation Assignments From Fold Resolution

Description

Dispatches a resolved cross-validation strategy to spatially stratified or leave-one-location-out assignment while preserving one assignment schema.

Usage

```
build_cross_validation_assignments_from_resolution(
  data_locations = NULL,
  data_fold_resolution = NULL,
  data_grid_calibration = NULL,
  n_repeats = 1L,
  seed = 900723L,
  assignment_source = "per_id"
)
```

Arguments

`data_locations`	Location table returned by [build_cross_validation_location_table()].
`data_fold_resolution`	One-row table returned by [resolve_cross_validation_fold_count()].
`data_grid_calibration`	Table returned by [compute_cross_validation_grid_calibration_from_resolution()].
`n_repeats`	Positive integer number of deterministic spatial assignment repeats.
`seed`	Non-negative integer assignment seed.
`assignment_source`	Non-empty character scalar recording assignment provenance.

Value

Tibble with the shared assignment columns plus 'cv_strategy' and 'assignment_source'. A no-holdout resolution returns a zero-row tibble with the same schema.

Examples

```
data_locations <-
  tibble::tibble(
    location_id = base::letters[1:6],
    coord_x_km = base::seq_len(6L),
    coord_y_km = base::seq_len(6L),
    n_samples = base::rep(1L, 6L),
    row_indices = base::as.list(base::seq_len(6L))
  )
data_resolution <-
  resolve_cross_validation_fold_count(6L, 5L)
build_cross_validation_assignments_from_resolution(
  data_locations = data_locations,
  data_fold_resolution = data_resolution,
  data_grid_calibration = tibble::tibble()
)
```