Make Cross-Validation Location Table

Description

Collapses aligned model samples to unique sampling locations for location-level cross-validation. Complete paleo cores and modern plots are represented by one row each.

Usage

```
build_cross_validation_location_table(
  data_sample_ids = NULL,
  data_coords_projected = NULL,
  location_column = "dataset_name"
)
```

Arguments

`data_sample_ids`	Data frame with one row per aligned model sample and a location identifier column named by 'location_column'.
`data_coords_projected`	Data frame with one row per sampling location, location identifiers in row names, and finite 'coord_x_km' and 'coord_y_km' columns.
`location_column`	Character scalar naming the location identifier column in 'data_sample_ids'. Defaults to '"dataset_name"'.

Details

Locations follow their first appearance in 'data_sample_ids'. Every sampled location must have exactly one projected coordinate row. Coordinate rows without aligned samples are omitted.

Value

Tibble with one row per sampled location and columns 'location_id', 'coord_x_km', 'coord_y_km', 'n_samples', and 'row_indices'. 'row_indices' is a list-column of integer row positions in 'data_sample_ids'.

Examples

```
data_sample_ids <-
  tibble::tibble(dataset_name = c("core_a", "core_a", "core_b"))
```

```
data_coords_projected <-
  data.frame(
    coord_x_km = c(10, 20),
    coord_y_km = c(30, 40),
    row.names = c("core_a", "core_b")
  )
build_cross_validation_location_table(
  data_sample_ids = data_sample_ids,
  data_coords_projected = data_coords_projected
)
```