Build Selected sjSDM Fold Artifacts

Description

Aligns prepared responses, selected-candidate probabilities, taxa, null probabilities, and sample metadata into one fold's public prediction and diagnostic artifacts. The function never fits a model.

Usage

```
build_sjsdm_selected_fold_artifacts(
  list_prepared_fold = NULL,
  list_fold_context = NULL,
  data_sample_ids = NULL,
  taxon_names = NULL,
  candidate_id = NULL,
  fit_seed = NULL,
  regularization_source = NULL,
  data_predicted = NULL,
  fold_status = "ok",
  error_message = NA_character_,
  converged = NA,
  actual_n_iter = NA_integer_,
  actual_n_sampling = NA_integer_,
  epochs_run = NA_integer_,
  linear_trend_slope = NA_real_,
  median_diff = NA_real_,
  early_stopping_triggered = NA
)
```

Arguments

`list_prepared_fold`	Valid prepared selected-fold inputs.

`list_fold_context`	Fold identifiers, held-out indices, sizes, and strategy.
`data_sample_ids`	Normalized sample metadata.
`taxon_names`	Full ordered response-taxon names.
`candidate_id`, `fit_seed`, `regularization_source`	Selected-candidate provenance.
`data_predicted`	Optional retained-taxon probability matrix. Missing for fit failures.
`fold_status`	'ok', 'fit_error', or 'prediction_error'.
`error_message`	Failure message, or a missing character value for successful predictions.
`converged`, `actual_n_iter`, `actual_n_sampling`, `epochs_run`	Final CV fitting convergence and actual-budget provenance.
`linear_trend_slope`, `median_diff`, `early_stopping_triggered`	Final convergence diagnostic values.

Value

Named list with 'data_predictions' and 'data_diagnostics'.