Build Trait Review Evidence Packets

Description

Builds candidate-, dataset-, and record-level evidence, including separate zero, negative, and non-finite counts, without changing records or decisions.

Usage

```
build_trait_review_evidence_packets(
  data_trait_records,
  data_trait_review_reconciliation,
  data_historical_review_scope,
  median_relative_tolerance = 0.01,
  iqr_relative_tolerance = 0.05
)
```

Arguments

`data_trait_records`	Current trait records retaining source identifiers.
`data_trait_review_reconciliation`	Current reconciliation table with one row per candidate.
`data_historical_review_scope`	Historical report index with extracted summary statistics.
`median_relative_tolerance`	Maximum relative median change for a stable historical summary.
`iqr_relative_tolerance`	Maximum relative IQR change for a stable historical summary.

Value

A named list containing 'data_candidate_evidence', 'data_dataset_evidence', and 'data_record_evidence'.

Examples

```
records <- tibble::tibble(
  taxon_name = "Taxon A",
```

```
  trait_domain_name = "Diaspore mass",
  trait_value = 1,
  dataset_id = 1L,
  dataset_name = "Dataset A",
  trait_name = "Seed mass"
)
reconciliation <- tibble::tibble(
  candidate_id = "candidate-a",
  taxon_name = "Taxon A",
  trait_domain_name = "Diaspore mass",
  n_taxon_outliers = 0L,
  implicit_none_proposal_eligible = TRUE,
  historical_scope_status = "confirmed_previous_review"
)
historical <- tibble::tibble(
  candidate_id = "candidate-a",
  historical_n_records = 1L,
  historical_median = 1,
  historical_iqr = 0
)
build_trait_review_evidence_packets(
  records,
  reconciliation,
  historical
)
```