Calibrate Cross-Validation Grid From Fold Resolution

Description

Runs spatial-grid calibration only when the resolved cross-validation strategy uses spatially stratified grouped folds.

Usage

```
compute_cross_validation_grid_calibration_from_resolution(
  data_locations = NULL,
  data_fold_resolution = NULL,
  candidate_grid_cell_sizes_km = NULL,
  n_repeats = 1L,
  occupancy_criterion = "median",
  target_locations_per_cell = NULL,
  lower_quantile_probability = 0.25,
  max_fold_location_difference = 1L,
  max_fold_sample_difference = Inf,
  seed = 900723L
)
```

Arguments

`data_locations`	Location table returned by [build_cross_validation_location_table()].
`data_fold_resolution`	One-row table returned by [resolve_cross_validation_fold_count()].
`candidate_grid_cell_sizes_km`	Numeric vector of candidate grid-cell widths in kilometres.
`n_repeats`	Positive integer number of deterministic assignment repeats.

`occupancy_criterion, target_locations_per_cell`	lower_quantile_probability,max_fold_location_difference, max_fold_sample_difference,seed Arguments passed to [compute_cross_validation_grid_calibration()].

Value

Grid-calibration tibble. Leave-one-location-out and no-holdout strategies return a zero-row tibble with the stable calibration schema.

Examples

```
data_locations <-
  tibble::tibble(
    location_id = base::letters[1:6],
    coord_x_km = base::seq_len(6L),
    coord_y_km = base::seq_len(6L),
    n_samples = base::rep(1L, 6L),
    row_indices = base::as.list(base::seq_len(6L))
  )
data_resolution <-
  resolve_cross_validation_fold_count(6L, 5L)
compute_cross_validation_grid_calibration_from_resolution(
  data_locations = data_locations,
  data_fold_resolution = data_resolution,
  candidate_grid_cell_sizes_km = c(1, 10)
)
```