Fit One sjSDM Regularization Candidate

Description

Fits one prepared training fold with regularization parameters from a deterministic candidate table.

Usage

```
fit_sjsdm_regularization_candidate(
  data_train_input = NULL,
  candidate = NULL,
  sel_abiotic_formula = NULL,
  config_model_fitting = NULL,
  seed = 900723L,
  device = "cpu",
  biotic = NULL,
  fit_function = fit_jsdm_model
)
```

Arguments

`data_train_input`	Fold-local training input returned by [prepare_sjsdm_cross_validation_fold()].
`candidate`	One-row candidate table containing 'candidate_id' and the six sjSDM regularization parameters.
`sel_abiotic_formula`	Abiotic model formula passed to [fit_jsdm_model()].
`config_model_fitting`	Active model-fitting configuration list.
`seed`	Deterministic integer seed for the candidate fit.
`device`	Device passed to [fit_jsdm_model()]. Defaults to '"cpu"'.

`biotic`	Optional sjSDM biotic structure. 'NULL' retains the regularized covariance structure created by [fit_jsdm_model()]. A diagonal structure disables residual cross-taxon associations for predictive decomposition.
`fit_function`	Injectable fit function. Defaults to [fit_jsdm_model()].

Details

The adapter keeps regularization forwarding in one tested place so tuning and selected-candidate reruns use identical fitting arguments.

Value

Fitted model object returned by 'fit_function'.