Load Configuration Value with Fallback

Description

Retrieves a configuration value from the active configuration. If the key is absent there, the function falls back to the same key in a named fallback configuration.

Usage

```
load_config_value_with_fallback(
  config_section,
  config_key,
  fallback_config = "default",
  file = here::here("config.yml")
)
```

Arguments

`config_section`	A single character string naming the configuration section to read, such as '"data_processing"'.
`config_key`	A single character string naming the configuration setting within 'config_section'.
`fallback_config`	A single character string naming the configuration to use when the active configuration does not define 'config_key'.
`file`	Path to the YAML configuration file. Defaults to 'here::here("config.yml")'.

Details

The function is intended for pipelines that keep a shared set of defaults in a dedicated configuration while still allowing project-specific overrides in the active configuration. If 'R_CONFIG_ACTIVE' is unset, the helper reads from '"default"'. Both the active config name and 'fallback_config' must exist in the YAML file.

Value

A scalar configuration value read from the active configuration or from 'fallback_config' when the active configuration does not define 'config_key'.

See Also

[load_active_config_value()], [load_config_value()]

Examples

```
load_config_value_with_fallback(
  config_section = "data_processing",
  config_key = "min_n_samples"
)
load_config_value_with_fallback(
  config_section = "data_processing",
  config_key = "ft_groups_min",
  fallback_config = "project_traits_reference"
)
```