Load Latest Functional-Type Classification

Description

Loads the most recent FT classification file for a given continental unit from 'Data/Processed/Traits/'. The file is produced by 'pipe_segment_traits_ft_clustering' in 'pipeline_traits_reference.R' and named 'data_functional_type_classification_continent_id_YYYY-MM-DD.qs'.

Usage

```
load_latest_functional_type_classification(

  continent_id,

  path_classification_directory = here::here("Data/Processed/Traits")

)
```

Arguments

`continent_id`	A single non-empty character string identifying the continental unit (e.g. '"europe"', '"america"', '"asia"'). Must match exactly with the 'scale_id' used when the FT classification was saved.
`path_classification_directory`	A single character string giving the directory that contains the FT classification '.qs' files. Default: 'here::here("Data/Processed/Traits")'.

Details

The function delegates path selection to [resolve_functional_type_classification_path()] and file loading to [load_functional_type_classification()].

Value

A tibble with two columns:

taxon_name

: Character. Taxon names resolved to finest available rank, matching the 'taxon_name' column in the global trait table.

functional_type

: Integer. Cluster label (1..'functional_type_group_count') assigned for this continental unit.

See Also

[assign_functional_type_clusters()], [resolve_functional_type_classification_path()], [load_functional_type_classification()]