Resolve Classification to Finest Rank

Description

For each taxon in a wide-format taxonomic classification table, selects the value from the finest available rank (species > genus > family > order > class > phylum > kingdom). The result maps every 'sel_name' to a single 'taxon_resolved' value taken from the finest non-'NA' rank available.

Usage

```
resolve_classification_to_finest_rank(

  data_classification_table,

  vec_taxon_column_name = "taxon_resolved"

)
```

Arguments

`data_classification_table`	A wide-format data frame (e.g. output of 'build_classification_table()') containing a 'sel_name' column plus taxonomic rank columns: 'kingdom', 'phylum', 'class', 'order', 'family', 'genus', and 'species'. All rank columns may contain 'NA' for unavailable ranks.
`vec_taxon_column_name`	A single non-empty character string giving the name of the output column that holds the resolved taxon name. Defaults to '"taxon_resolved"'.

Details

The function pivots the seven rank columns to long format, removes 'NA' rank values, assigns a numeric rank order (kingdom = 1, …, genus = 6, species = 7), and for each 'sel_name' retains the row with the highest rank order via 'dplyr::slice_max()'. Ties are broken arbitrarily ('with_ties = FALSE'). The rank order and the intermediate 'rank' column are dropped before returning, leaving only 'sel_name' and the column named by 'vec_taxon_column_name'.

Value

A tibble with two columns: 'sel_name' (character) and the column named by 'vec_taxon_column_name' (character, default '"taxon_resolved"'). One row is returned per unique 'sel_name'. The resolved column holds the taxon name at the finest available rank, or 'NA' if no rank column was non-'NA'.

See Also

[build_classification_table()]