Resolve Cross-Validation Fold Count

Description

Resolves the smallest viable location-level fold count from a default toward leave-one-location-out while preserving a minimum training-location count.

Usage

```
resolve_cross_validation_fold_count(
  n_locations = NULL,
  min_train_locations = NULL,
  default_folds = 5L
)
```

Arguments

`n_locations`	Single positive integer. Number of unique sampling locations available.
`min_train_locations`	Single positive integer. Minimum number of locations required in every training partition and in the full model.
`default_folds`	Single integer greater than one. Preferred grouped fold count. Defaults to '5L'.

Details

Balanced grouped folds are assessed using the largest possible test fold, 'ceiling(n_locations / effective_folds)'. If the preferred fold count would remove too many locations, fold count increases until every training partition is viable. A fold count equal to 'n_locations' is classified as leave-one-location-out. A full-model-viable ID with no viable holdout is classified for tier-pooled regularization. Other sample, response, and MEM checks belong to the separate CV feasibility assessment.

Value

One-row tibble with 'n_locations', 'default_folds', 'effective_folds', 'min_train_locations', 'min_training_locations_actual', 'cv_strategy', and 'cv_feasibility_status'. 'effective_folds' is 'NA' when location-level holdout is infeasible.

Examples

```
resolve_cross_validation_fold_count(
  n_locations = 7L,
  min_train_locations = 5L
)
```