Run a Main Analysis Stage

Description

Runs an ordered table of main-analysis component scripts in isolated R subprocesses, streams their output into live logs, and records statuses.

Usage

```
run_main_analysis_stage(
  stage_id = NULL,
  data_components = NULL,
  run_id = NULL,
  continue_on_error = FALSE,
  next_stage_script = NULL,
  runner_function = processx::run,
  log_root = here::here("Data", "Temp", "Main_analysis_execution"),
  verbose = TRUE
)
```

Arguments

`stage_id`	Non-empty identifier for the numbered main-analysis stage.
`data_components`	Data frame with unique 'component_id' and 'script_path' columns. Optional list-columns 'arguments' and 'environment' supply subprocess arguments and environment variables.
`run_id`	Non-empty identifier shared by all component batches in one stage run.
`continue_on_error`	Logical scalar. If 'TRUE', all independent components are attempted before the stage fails. If 'FALSE', execution stops after the first failure.
`next_stage_script`	Optional project-relative path printed after a successful stage.
`runner_function`	Injectable subprocess runner. Defaults to [processx::run()].

`log_root`	Directory under which stage logs and status CSV files are written.
`verbose`	Logical. If 'TRUE' (default), progress messages are printed to the console.

Value

Tibble with one row per attempted component and its exit status and log.