Monitor Pipeline Progress

Description

Opens the official 'targets' dashboard for a pipeline target store.

Usage

```
run_pipeline_progress_monitor(
  sel_script,
  sel_config,
  store_suffix = NULL,
  seconds_refresh = 10,
  sel_initial_display = "branches",
  flag_refresh_automatically = FALSE,
  verbose = TRUE
)
```

Arguments

`sel_script`	Path to the pipeline script, relative to the project root or absolute.
`sel_config`	Configuration key in 'config.yml' whose 'target_store' contains the selected pipeline output.
`store_suffix`	Optional nested target store identifier inserted between 'target_store' and the pipeline script name, such as '"europe"' or '"eu_r005_l014"'.
`seconds_refresh`	Positive finite refresh interval in seconds. Used only when automatic refresh is enabled in the dashboard. Default is '10'.
`sel_initial_display`	Initial official 'targets' dashboard tab. One of '"summary"', '"branches"', '"progress"', '"graph"', or '"about"'.

`flag_refresh_automatically`	Logical indicating whether dashboard periodic refresh starts enabled. Default is 'FALSE'.
`verbose`	Logical indicating whether to display launch information. Default is 'TRUE'.

Details

The target store is resolved using the same layout as [run_pipeline()]: 'target_store/pipeline_name/' when 'store_suffix' is 'NULL', and 'target_store/store_suffix/pipeline_name/' otherwise. The app always uses 'targets_only = TRUE' and 'outdated = FALSE' to keep monitoring fast. Stop a running monitor with 'Ctrl+C'.

Value

No return value. The dashboard runs in the foreground until stopped.

See Also

[run_pipeline()], [targets::tar_watch_ui()], [targets::tar_watch_server()]

Examples

```
## Not run:

run_pipeline_progress_monitor(

  sel_script = "R/Pipelines/pipeline_paleo_spatial_resolution.R",

  sel_config = "project_paleo_spatial_continental",

  store_suffix = "europe"

)


run_pipeline_progress_monitor(

  sel_script = "R/Pipelines/pipeline_paleo_core.R",

  sel_config = "project_cz_paleo"

)


## End(Not run)
```