Run sjSDM Tuning Candidates for One Fold

Description

Prepares one fold once, then fits, predicts, and scores every regularization candidate while preserving failures as compact status rows.

Usage

```
run_sjsdm_tuning_fold_candidates(
  data_candidates = NULL,
  list_fold_context = NULL,
  prepare_fold_function = NULL,
  fit_function = NULL,
  predict_function = NULL,
  score_function = score_sjsdm_tuning_predictions,
  seed = 900723L,
  epsilon = 1e-06,
  retain_prediction_cache = FALSE
)
```

Arguments

`data_candidates`	Candidate table returned by [build_sjsdm_regularization_candidates()].
`list_fold_context`	Fold metadata returned by [build_sjsdm_tuning_fold_context()].
`prepare_fold_function`, `fit_function`, `predict_function`, `score_function`	Injectable fold preparation, fit, prediction, and scoring functions documented by [run_sjsdm_tuning_candidates()].
`seed`	Non-negative base integer used to derive candidate fit and score seeds.

`epsilon`	Probability clipping tolerance passed to [score_sjsdm_tuning_predictions()].
`retain_prediction_cache`	Logical. When true, return compact prepared-fold metadata and candidate probability matrices alongside the unchanged tuning table.

Value

Compact candidate-by-fold tuning table with metrics and structured status. When 'retain_prediction_cache' is true, returns a named list containing that table and a compact fold prediction cache without fitted model objects.