Run One sjSDM Unit Tuning Round

Description

Runs one cumulative tuning round across isolated unit stores while preserving the round environment variable and first-round semantics.

Usage

```
run_sjsdm_tuning_unit_round(
  round_id = NULL,
  unit_pipeline = NULL,
  tuning_target_names = NULL,
  unit_store_suffixes = NULL,
  prebuild_round = FALSE,
  fresh_round = FALSE,
  run_pipeline_function = run_pipeline,
  vec_allowed_profile_roles = base::c("main", "smoke"),
  vec_allowed_profile_statuses = "active",
  unit_target_names = NULL,
  verbose = TRUE
)
```

Arguments

`round_id`, `unit_pipeline`, `tuning_target_names`, `unit_store_suffixes`	Round identifier and unit execution inputs.
`prebuild_round`, `fresh_round`	First-round interpolation and store-reset flags.
`run_pipeline_function`	Injectable pipeline runner.
`vec_allowed_profile_roles`, `vec_allowed_profile_statuses`	Allowed profile metadata forwarded to the runner.
`unit_target_names`	Optional named list of per-unit target requests from verified preparation. Empty requests are expected infeasible and never

	sent to the runner.
`verbose`	Logical controlling unit messages.

Value

Tibble with one row per unit and its pipeline status and error message.