prepare_sjsdm_tuning_folds.R

October 22, 2026

Contents

prepare_sjsdm_tuning_folds 1

Index **3**

`prepare_sjsdm_tuning_folds` *Prepare sjSDM Tuning Folds*

Description

Prepares every repeat/fold partition exactly once for reuse by granular candidate work items.

Usage

```
prepare_sjsdm_tuning_folds(
  data_assignments = NULL,
  prepare_fold_function = NULL,
  cached_folds_function = NULL
)
```

Arguments

`data_assignments`
: Cross-validation assignments accepted by [run_sjsdm_tuning_candidates()].

`prepare_fold_function`
: Injectable preparation function documented by [run_sjsdm_tuning_candidates()].

`cached_folds_function`
: Optional zero-argument reader of prior fold records. Current folds are always prepared first. Successful analytically identical records reuse the original cached object, retaining its operational measurements. Unreadable or analytically different caches are ignored.

Details

Exact equality uses the version-five calibration content contract. Only operational timing and spatial memory measurements are excluded; all analytical fields and fold contexts remain part of the comparison.

Value

List with one keyed entry per fold. Each entry contains fold context, preparation timing, and either the prepared inputs or a structured error.

Examples

```
## Not run:
prepare_sjsdm_tuning_folds(
  data_assignments = assignments,
  prepare_fold_function = prepare_fold
)

## End(Not run)
```

Index

prepare_sjsdm_tuning_folds, 1