# run_sjsdm_cv_calibration_rung.R

October 22, 2026

## Contents

run_sjsdm_cv_calibration_rung . . . . . 1

**Index** **3**

---

`run_sjsdm_cv_calibration_rung`
*Run One sjSDM CV Calibration Budget Rung*

---

### Description

Fits and scores every regularization candidate over cached prepared folds for one or more repeats at one fixed iteration and sampling budget.

### Usage

```
run_sjsdm_cv_calibration_rung(
  data_candidates = NULL,
  list_prepared_folds = NULL,
  data_budget = NULL,
  sel_abiotic_formula = NULL,
  config_sjsdm_cv_fitting = NULL,
  repeat_ids = 1L,
  fold_ids = NULL,
  work_checkpoint_file = NULL,
  calibration_stage = "calibration",
  seed = 900723L,
  device = "gpu",
  candidate_fit_function = fit_sjsdm_cross_validation_candidate,
  predict_function = predict_sjsdm_probability_matrix,
  score_function = score_sjsdm_joint_tuning_predictions,
  verbose = TRUE
)
```

## Arguments

| | |
|---|---|
| `data_candidates` | Complete regularization candidate table. |
| `list_prepared_folds` | Cached fold records from [prepare_sjsdm_tuning_folds()]. |
| `data_budget` | One-row calibration ladder entry. |
| `sel_abiotic_formula`, `config_sjsdm_cv_fitting` | Model formula and validated structural CV fitting configuration. |
| `repeat_ids` | Integer repeats to execute. |
| `fold_ids` | Optional positive integer fold IDs to retain. 'NULL' keeps all folds. |
| `work_checkpoint_file` | Optional '.qs' file that persists each completed candidate-fold result. |
| `calibration_stage` | Character label used in progress messages and checkpoint provenance. |
| `seed`, `device` | Deterministic seed and fitting device. |
| `candidate_fit_function`, `predict_function`, `score_function` | Injectable fitting, prediction, and scoring backends. |
| `verbose` | Logical. If 'TRUE', progress is printed to the console. |

## Value

List containing fold-level benchmark evidence and attempt-level provenance.

# Index

run_sjsdm_cv_calibration_rung, 1