run_sjsdm_tuning_unit_round.R

October 22, 2026

Contents

run_sjsdm_tuning_unit_round 1

Index **3**

`run_sjsdm_tuning_unit_round`
Run One sjSDM Unit Tuning Round

Description

Runs one cumulative tuning round across isolated unit stores while preserving the round environment variable and first-round semantics.

Usage

```
run_sjsdm_tuning_unit_round(
  round_id = NULL,
  unit_pipeline = NULL,
  tuning_target_names = NULL,
  unit_store_suffixes = NULL,
  prebuild_round = FALSE,
  fresh_round = FALSE,
  run_pipeline_function = run_pipeline,
  vec_allowed_profile_roles = base::c("main", "smoke"),
  vec_allowed_profile_statuses = "active",
  unit_target_names = NULL,
  verbose = TRUE
)
```

Arguments

`round_id`, `unit_pipeline`, `tuning_target_names`, `unit_store_suffixes`
: Round identifier and unit execution inputs.

`prebuild_round`, `fresh_round`
: First-round interpolation and store-reset flags.

`run_pipeline_function`
: Injectable pipeline runner.

`vec_allowed_profile_roles`, `vec_allowed_profile_statuses`
: Allowed profile metadata forwarded to the runner.

`unit_target_names`
: Optional named list of per-unit target requests from verified preparation. Empty requests are expected infeasible and never sent to the runner.

`verbose`
: Logical controlling unit messages.

Value

Tibble with one row per unit and its pipeline status and error message.

Index

run_sjsdm_tuning_unit_round, 1