run_sjsdm_unit_fitting_preflight.R

October 22, 2026

Contents

run_sjsdm_unit_fitting_preflight 1

Index **3**

`run_sjsdm_unit_fitting_preflight`
Revalidate Spatial Unit Preparation Before Fitting

Description

Reads prepared-fold evidence per resolution and reattempts only registered failed preparation roots through the canonical runner. Current input hashes are checked by targets; stale metadata alone never authorizes an exclusion.

Usage

```
run_sjsdm_unit_fitting_preflight(
  unit_pipeline,
  target_store,
  scale_ids,
  resolution_ids,
  run_pipeline_function = run_pipeline,
  load_metadata_function = load_targets_store_metadata,
  diagnose_endpoints_function = diagnose_sjsdm_cv_preparation_endpoints,
  read_target_function = targets::tar_read_raw,
  verbose = TRUE
)
```

Arguments

`unit_pipeline`, `target_store`
: Pipeline script and root store path.

`scale_ids`, `resolution_ids`
: Unique requested units and pipeline resolution suffixes.

`run_pipeline_function`, `load_metadata_function`
: Injectable canonical runner and cached metadata loader.

`diagnose_endpoints_function`, `read_target_function`
: Injectable endpoint checker and target reader.

`verbose`
: Logical controlling progress messages.

Details

No tuning or model target is requested. Successful preparation is not rebuilt by this check. A failed shared root excludes all its resolutions; a resolution-specific root never excludes another resolution.

Value

A tibble of unit-resolution fitting statuses, reasons and root evidence. Missing evidence and unexplained errors block fitting after all units have been checked. Changed formerly infeasible inputs require stage 01 again.

Examples

```
## Not run:
run_sjsdm_unit_fitting_preflight(
  unit_pipeline = "R/Pipelines/pipeline_modern_spatial_resolution.R",
  target_store = "Data/targets/modern_spatial_regional",
  scale_ids = "eu_r005", resolution_ids = c("genus", "family")
)

## End(Not run)
```

Index

run_sjsdm_unit_fitting_preflight, 1