

build_sjsdm_candidate_fold_result.R

August 11, 2026

Contents

build_sjsdm_candidate_fold_result 1

Index 3

build_sjsdm_candidate_fold_result
Build One sjSDM Candidate-Fold Result

Description

Constructs one typed tuning row and its compact prediction-cache record for a completed or failed candidate lifecycle.

Usage

```
build_sjsdm_candidate_fold_result(  
  data_candidate = NULL,  
  list_fold_context = NULL,  
  fit_seed = NA_integer_,  
  score_seed = NA_integer_,  
  fit_status = NULL,  
  error_message = NA_character_,  
  data_metrics = NULL,  
  data_predicted = NULL,  
  fit_seconds = NA_real_,  
  prediction_seconds = NA_real_,  
  scoring_seconds = NA_real_  
)
```

Arguments

`data_candidate` One-row candidate table with the candidate identifier and six parameters.
`list_fold_context` Fold context containing identifiers, sizes, and the CV strategy.
`fit_seed, score_seed` Derived candidate seeds, or typed missing integers before candidate work.

<code>fit_status</code>	One of 'preparation_error', 'fit_error', 'prediction_error', 'scoring_error', or 'ok'.
<code>error_message</code>	Character failure message, or a missing character value for success.
<code>data_metrics</code>	Optional named list of the five candidate scoring metrics.
<code>data_predicted</code>	Optional held-out probability matrix. Fitted model objects are never stored.
<code>fit_seconds, prediction_seconds, scoring_seconds</code>	Candidate lifecycle timings in seconds.

Value

Named list containing one-row 'data_tuning' and 'list_prediction'.

Index

`build_sjsdm_candidate_fold_result`, [1](#)