

build_sjsdm_predictor_comparison_structure.R

August 11, 2026

Contents

build_sjsdm_predictor_comparison_structure	1
Index	3

build_sjsdm_predictor_comparison_structure	
<i>Configure an sjSDM Predictor Structure</i>	

Description

Creates a model-fitting configuration and abiotic formula for a controlled predictor-component comparison.

Usage

```
build_sjsdm_predictor_comparison_structure(  
  predictor_structure = NULL,  
  config_model_fitting = NULL,  
  model_formula = NULL  
)
```

Arguments

<code>predictor_structure</code>	One of "intercept_only", "abiotic_only", "spatial_only", "abiotic_spatial", or "abiotic_spatial_no_associations".
<code>config_model_fitting</code>	Base model-fitting configuration. It is copied before 'use_spatial' is set.
<code>model_formula</code>	Full abiotic model formula. Intercept-only and spatial-only structures replace it with '~ 1' because sjSDM requires an environmental component.

Details

This helper changes predictor inclusion only. Regularization, folds, seeds, fitting device, response filtering, and all other settings remain controlled by the caller. The intercept-only structure can retain sjSDM's biotic covariance and is therefore distinct from a fold-prevalence null.

Value

Named list containing the structure identifier, component flags, modified model-fitting configuration, and formula.

Examples

```
build_sjsdm_predictor_comparison_structure(  
  predictor_structure = "abiotic_only",  
  config_model_fitting = list(use_spatial = TRUE),  
  model_formula = stats::as.formula("~ age")  
)
```

Index

build_sjsdm_predictor_comparison_structure,
[1](#)