

build_sjsdm_tier_tuning_artifact.R

August 11, 2026

Contents

build_sjsdm_tier_tuning_artifact	1
Index	3

build_sjsdm_tier_tuning_artifact
<i>Build sjSDM Tier Tuning Artifact</i>

Description

Runs compatible tier-level tuning aggregation and publishes an immutable selected-candidate artifact with complete provenance.

Usage

```
build_sjsdm_tier_tuning_artifact(  
  data_tuning_summary = NULL,  
  created_at = NULL,  
  include_sample_weighted = TRUE  
)
```

Arguments

data_tuning_summary	Source-ID tuning summaries accepted by [aggregate_sjsdm_tuning_by_tier()].
created_at	Single POSIX date-time supplied explicitly by the orchestration layer.
include_sample_weighted	Logical passed to [aggregate_sjsdm_tuning_by_tier()].

Details

The artifact always selects the equal-ID result. Sample-weighted selection is retained only as a sensitivity report.

Value

Named list containing artifact, source_candidate_loss, candidate_aggregation, and selection_sensitivity. The artifact is a one-row tibble with selected parameters, model context, source IDs, selection rule, candidate-table hash, creation time, and schema version.

Examples

```
## Not run:
build_sjsdm_tier_tuning_artifact(
  data_tuning_summary = data_tuning_summary,
  created_at = base::as.POSIXct(
    "2026-07-05 12:00:00",
    tz = "UTC"
  )
)

## End(Not run)
```

Index

build_sjsdm_tier_tuning_artifact, [1](#)