

build_trait_table.R

August 11, 2026

Contents

build_trait_table 1

Index 3

build_trait_table	<i>Build Wide-Format Species x Traits Table</i>
-------------------	---

Description

Pivots a long-format aggregated trait data frame into a wide-format table with one row per taxon and one column per trait domain. This produces the genus x traits matrix used for functional type assignment.

Usage

```
build_trait_table(  
  data_aggregated_trait_values,  
  taxon_column = "taxon_name",  
  trait_domain_column = "trait_domain_name",  
  trait_value_column = "trait_value_aggregated"  
)
```

Arguments

data_aggregated_trait_values
A data frame in long format with one row per taxon x trait combination. Must contain at least the columns specified by 'taxon_column', 'trait_domain_column', and 'trait_value_column'.

taxon_column
A character string naming the column containing taxon (genus) names. Default: "taxon_name".

trait_domain_column
A character string naming the column containing trait domain names. Default: "trait_domain_name".

trait_value_column
A character string naming the column containing aggregated trait values. Default: "trait_value_aggregated".

Details

Wraps `tidyr::pivot_wider()`. If a taxon x trait combination appears more than once, only the first value is retained (`'values_fn = dplyr::first'`).

Value

A tibble with one row per taxon and one column per trait domain, plus the taxon name column. Column names for traits are taken directly from the values in `'trait_domain_column'`.

See Also

[`aggregate_trait_values()`], [`summarise_trait_coverage()`]

Index

`build_trait_table`, [1](#)