

compute_community_presence_absence.R

August 11, 2026

Contents

compute_community_presence_absence 1

Index 3

compute_community_presence_absence
Compute Community Presence-Absence Matrix

Description

Computes a binary presence-absence matrix from numeric community proportions or counts. Positive values become ‘1L’; zeros and missing values become ‘0L’.

Usage

```
compute_community_presence_absence(mat_community = NULL)
```

Arguments

`mat_community` A numeric matrix with samples as rows and taxa as columns, as returned by ‘prepare_community_for_fit()’. Values must be non-negative.

Details

Presence-absence conversion before ‘filter_constant_taxa()’ is essential when using a binomial error family: a taxon recorded at non-zero varying proportions in every sample has positive SD on the proportion scale but becomes a constant-1 column after conversion inside the model, causing implicit intercept saturation. Applying this function first ensures that ‘filter_constant_taxa()’ removes such taxa before they reach the model.

For other error families (e.g., Gaussian, hurdle models) the raw proportional matrix should be passed to ‘filter_constant_taxa()’ directly; use the ‘error_family’ configuration key to control this choice in the pipeline.

Value

An integer matrix with the same dimensions and dimnames as ‘mat_community’, containing only ‘0L’ and ‘1L’.

See Also

[prepare_community_for_fit()], [filter_constant_taxa()], [build_jsdm_fit_input()]

Examples

```
mat_community <-  
  base::matrix(  
    base::c(0, 0.25, NA_real_, 1),  
    nrow = 2  
  )  
  
compute_community_presence_absence(  
  mat_community = mat_community  
)
```

Index

`compute_community_presence_absence`, [1](#)