

# load\_continental\_trait\_records\_from\_vegvault.R

August 11, 2026

## Contents

|                                                        |          |
|--------------------------------------------------------|----------|
| load_continental_trait_records_from_vegvault . . . . . | 1        |
| <b>Index</b>                                           | <b>3</b> |

---

|                                                     |
|-----------------------------------------------------|
| load_continental_trait_records_from_vegvault        |
| <i>Load Continental Trait Records from VegVault</i> |

---

## Description

Loads raw trait data from VegVault for a single continental bounding box, removes incomplete records, and translates numeric taxon IDs to taxon names. Optionally prints progress messages.

## Usage

```
load_continental_trait_records_from_vegvault(  
  data_continental_unit,  
  vec_trait_domain_names,  
  path_vegvault = here::here("Data/Input/VegVault.sqlite"),  
  verbose = TRUE  
)
```

## Arguments

|                        |                                                                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| data_continental_unit  | A single-row data frame (one continental unit from the spatial grid) with columns 'scale_id', 'x_min', 'x_max', 'y_min', and 'y_max'.              |
| vec_trait_domain_names | A non-empty character vector of trait domain names to extract (e.g. 'c("Specific leaf area (SLA)", "Plant height vegetative")').                   |
| path_vegvault          | A single character string giving the path to the VegVault SQLite database (default: 'here::here("Data/Input/VegVault.sqlite")').                   |
| verbose                | A single logical value. If 'TRUE' (default), progress messages are printed via 'cli::cli_inform()'. Set to 'FALSE' to suppress all console output. |

**Details**

The function performs the following steps:

1. Validates all input arguments.
2. Derives the bounding-box limits and scale identifier from 'data\_continental\_unit'.
3. Calls `[load_trait_records_from_vegvault()]` to retrieve raw records.
4. Calls `[filter_complete_trait_records()]` to drop incomplete rows.
5. Calls `[resolve_trait_taxon_ids()]` to replace numeric IDs with taxon names.
6. Returns the final tibble with taxon-name columns only.

**Value**

A tibble with columns 'taxon\_name', 'trait\_domain\_name', 'trait\_name', and 'trait\_value', containing the cleaned and ID-resolved trait records for the supplied continental unit.

**See Also**

`[load_trait_records_from_vegvault()]`, `[filter_complete_trait_records()]`, `[resolve_trait_taxon_ids()]`

# Index

load\_continental\_trait\_records\_from\_vegvault,  
[1](#)