

# resolve\_spatial\_mev\_strategy.R

August 11, 2026

## Contents

resolve\_spatial\_mev\_strategy . . . . . 1

**Index** 3

---

resolve\_spatial\_mev\_strategy  
*Resolve the Shared Spatial MEM Construction Strategy*

---

## Description

Validates shared Moran eigenvector construction settings and resolves "auto" to the exact or fast implementation using only the number of input spatial locations.

## Usage

```
resolve_spatial_mev_strategy(  
  strategy = NULL,  
  n_locations = NULL,  
  n_mev = NULL,  
  exact_max_locations = NULL,  
  fast_eigenvectors = NULL  
)
```

## Arguments

|                     |                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------|
| strategy            | Character scalar. One of "exact", "fast", or "auto".                                                |
| n_locations         | Positive integer giving the number of input spatial locations.                                      |
| n_mev               | Positive integer giving the number of public Moran eigenvectors requested.                          |
| exact_max_locations | Positive integer giving the largest input allowed to use dense exact construction.                  |
| fast_eigenvectors   | Positive integer giving the low-rank basis size for fast construction. It must be at least 'n_mev'. |

**Value**

Named list containing the requested and selected strategies, strategy version, validated counts, and shared exact/fast settings.

**Examples**

```
resolve_spatial_mev_strategy(  
  strategy = "auto",  
  n_locations = 2000L,  
  n_mev = 3L,  
  exact_max_locations = 1999L,  
  fast_eigenvectors = 200L  
)
```

# Index

`resolve_spatial_mev_strategy`, [1](#)