

# aggregate\_trait\_values.R

April 21, 2026

## Contents

|                        |          |
|------------------------|----------|
| aggregate_trait_values | 1        |
| <b>Index</b>           | <b>3</b> |

---

aggregate\_trait\_values

*Aggregate Trait Values to Single Value per Group*

---

## Description

Aggregates a long-format trait data frame to one row per group (by default per taxon x trait combination) using a specified summary function. Intended to be applied after outlier removal.

## Usage

```
aggregate_trait_values(  
  data,  
  trait_col = "trait_value",  
  group_cols = c("taxon_name", "trait_domain_name"),  
  fn = c("median", "mean")  
)
```

## Arguments

|            |                                                                                                                          |
|------------|--------------------------------------------------------------------------------------------------------------------------|
| data       | A data frame in long format with at least the columns specified by 'trait_col' and 'group_cols'.                         |
| trait_col  | A character string naming the numeric column containing trait values. Default: "trait_value".                            |
| group_cols | A character vector of column names used to define groups for aggregation. Default: c("taxon_name", "trait_domain_name"). |
| fn         | A character string specifying the aggregation function. One of "median" (default) or "mean". Matched with 'match.arg()'. |

## Details

The 'fn' argument is processed via 'match.arg()', so partial matching is supported (e.g. 'fn = "med"' resolves to "median").

**Value**

A data frame with one row per unique combination of ‘group\_cols’ and a new column ‘trait\_value\_aggregated’ containing the aggregated value.

**See Also**

[filter\_trait\_outliers()], [make\_trait\_table()]

# Index

`aggregate_trait_values`, [1](#)