

get_functional_type_classification.R

April 21, 2026

Contents

get_functional_type_classification	1
Index	3

get_functional_type_classification	
<i>Get Functional-Type Classification for a Continental Unit</i>	

Description

Loads the most recent FT classification file for a given continental unit from 'Data/Processed/Traits/'.
The file is produced by 'pipe_segment_trait_ft_clustering' in 'pipeline_traits.R' and named 'data_ft_classification_continent_id-MM-DD.qs'.

Usage

```
get_functional_type_classification(  
  continent_id,  
  path_processed = here::here("Data/Processed/Traits")  
)
```

Arguments

continent_id	A single non-empty character string identifying the continental unit (e.g. "eu-rope", "america", "asia"). Must match exactly with the 'scale_id' used when the FT classification was saved.
path_processed	A single character string giving the directory that contains the FT classification 'qs' files. Default: 'here::here("Data/Processed/Traits")'.

Details

The function lists all 'qs' files in 'path_processed' matching the pattern 'data_ft_classification_continent_id_*.qs', selects the file with the most recent date suffix (ISO 8601: YYYY-MM-DD), and reads it via 'qs2::qs_read()'. If no matching file is found the function aborts with an informative error.

Value

A tibble with two columns:

taxon_name Character. Taxon names resolved to finest available rank, matching the 'taxon_name' column in the global trait table.

functional_type Integer. Cluster label (1..'number_of_ft_groups') assigned for this continental unit.

See Also

[cluster_functional_types()]

Index

`get_functional_type_classification`, [1](#)